

**SCAG**  
POWER EQUIPMENT



*The extreme  
cutting machine.*

## Specifications

<b>Engine Options:</b>	31hp Briggs Daihatsu Vanguard turbo diesel, liquid-cooled, 3-cylinder
<b>Fuel Capacity/Design:</b>	10 gallons, single fuel tank mounted low in the center of the mower to lower the center-of-gravity and improve hillside stability and traction.
<b>Travel Control:</b>	Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes.
<b>Ground Speed:</b>	10.5mph forward, 5mph reverse
<b>Main Frame Construction:</b>	Double tube, steel frame, full length, fully welded
<b>Drive Tires:</b>	24 x 12 - 12, 4 ply
<b>Caster Tires:</b>	13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic
<b>Caster Wheel Bearings:</b>	Tapered roller bearings
<b>Front Caster Arm Design:</b>	Bolt-on for easy replacement if necessary
<b>Hydraulic Pumps:</b>	Dual Pumps; 21cc displacement, Hydro-Gear BDP-21L
<b>Hydraulic Oil Cooler:</b>	Yes - 4 qt system capacity with auxiliary oil cooler
<b>Hydraulic Oil Filter:</b>	10 micron
<b>Hydraulic Wheel Motors:</b>	Dual Ross 22ci heavy-duty motors with extra large shafts
<b>Electrical System:</b>	12 Volt battery. Alternator, 40amp charging. Solenoid shift starter.

**WWW.SCAG.COM**

(Continued)

**SCAG**

- Belts:** Kevlar cord. Self-adjusting, spring-loaded self-tightening
- Drive/Load Pulleys:** Split-steel design -- stronger and lighter weight than cast-iron
- Instrument Panel :** Ammeter, key switch, throttle, manual choke, BBC switch, water temp gauge
- Command-Comfort Operator's Station:**
- Torsion spring suspension seat, fully adjustable, with arm rests.
  - "Quick-Fit" steering control levers feature incredible range of adjustment for optimal comfort and control
  - 3-Position adjustable deck lift foot pedal allows for easy deck lift for all operators
- PTO - Electric Clutch:** Ogura GT5 - 350 ft lb / adjustable air-gap
- Cutter Decks:** 61" Velocity Plus or 72" Advantage Deck. Floating, adjustable, anti-scalping design.
- Cutter Deck Construction:** Tri-Plate, welded with 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.
- Cutter Deck Drive:** Drive shaft driven -- eliminates belt slip for increased reliability & longevity
- Number of Anti-Scalp Wheels:**
- 61": 9 wheels in 7 positions
  - 72": 9 wheels in 7 positions
- Cutter Deck Spindles:** Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
- Cutter Deck Height Adjustment:**
- Foot pedal lift with self-locking mechanism at transport position
- Cutting Range:** 1" to 6" in 1/4" increments
- Number of Cutter Blades:** 3 Marbain blades
- Total Length:**
- 61" models: 92"
  - 72" models: 94"
- Total Width (with discharge chute in mowing position):**
- 61" models: 73.5"
  - 72" models: 83"
- Total Width (with discharge chute in transport position):**
- 61" models: 62"
  - 72" models: 73"
- Height (with ROPS):** 67.5"
- Height (with ROPS folded):** 56.5"
- Weight (with ROPS):**
- 1685 lbs.
- Warranty:**
- 2 Yr. Mower Warranty—Parts & labor.
  - 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
  - 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
  - 2 Yr. Engine Warranty—Minimum of a two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice.

[WWW.SCAG.COM](http://WWW.SCAG.COM)