

SCAG
POWER EQUIPMENT

TURF Tiger

In a class by itself.



Specifications

Engine Options:

- 27hp Kohler, air-cooled, twin cylinder, horizontal shaft
- 27hp Kawasaki, liquid-cooled, twin cylinder, horizontal shaft
- 29hp Kawasaki, liquid-cooled, twin cylinder, horizontal shaft, Digital Fuel Injection
- 35hp Briggs Vanguard Big Block, air-cooled, V-Twin
- 35hp Briggs Vanguard Big Block, liquid-cooled, V-Twin

Fuel Capacity/Design:

10 gallons, single fuel tank mounted low in the center of the mower to lower the center-of-gravity and improve hillside stability and traction.

Travel Control:

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes.

Ground Speed:

- 12mph forward, 5 mph reverse (29hp+ models)
- 10mph forward, 5mph reverse (other models)

Main Frame Construction:

Double tube, steel frame, full length, fully welded

Drive Tires:

- 52": 23 x 10.5 -12, 4 ply
- 61" & 72": 24 x 12 - 12, 4 ply

Caster Tires:

- 52": 13 x 5 - 6, 4 ply; Flat-Free
- 61" & 72": 13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Hydraulic Pumps:

Dual Pumps; 16cc displacement, Hydro-Gear BDP-16A

Hydraulic Oil Cooler:

Yes - 4 qt system capacity with auxiliary oil cooler

Hydraulic Oil Filter:

10 micron

Hydraulic Wheel Motors:

Dual Ross (29hp+ models) or Hydro-Gear/Danfoss (27hp models)
15ci heavy-duty motors with extra large shafts

Electrical System:

12 Volt battery. Alternator, 15amp charging. Solenoid shift starter.

WWW.SCAG.COM

(Continued)

SCAG

- Belts:** Kevlar cord. Self-adjusting, spring-loaded self-tightening
- Drive/Load Pulleys:** Split-steel design -- stronger and lighter weight than cast-iron
- Instrument Panel :** Ammeter, key switch, throttle, manual choke, BBC switch, water temp gauge (on liquid-cooled models)
- Command-Comfort Operator's Station:**
- Torsion spring suspension seat, fully adjustable, with arm rests (29hp+ models). High-back Soft-Ride seat, adjustable with padded arm rests (27hp models).
 - "Quick-Fit" steering control levers feature incredible range of adjustment for optimal comfort and control
 - 3-Position adjustable deck lift foot pedal allows for easy deck lift for all operators
- PTO - Electric Clutch:**
- Ogura GT3.5 - 250 ft lb / adjustable air-gap
 - Ogura GT5 - 350 ft lb (on 35hp BV) / adjustable air-gap
- Cutter Decks:** 52" & 61" Velocity Plus, or 72" Advantage Decks. Floating, adjustable, anti-scalping design.
- Cutter Deck Construction:** Tri-Plate, welded: 52" with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates. 61" & 72" with 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.
- Cutter Deck Drive:** Drive shaft driven -- eliminates belt slip for increased reliability & longevity
- Number of Anti-Scalp Wheels:**
- 52": 9 wheels in 7 positions
 - 61": 9 wheels in 7 positions
 - 72": 9 wheels in 7 positions
- Cutter Deck Spindles:** Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
- Cutter Deck Height Adjustment:** Foot pedal (3-position adjustable) lift with self-locking mechanism at transport position
- Cutting Range:** 1" to 6" in 1/4" increments
- Number of Cutter Blades:** 3 Marbain blades
- Total Length:**
- 52" models: 82.5"
 - 61" models: 87.5"
 - 72" models: 90"
- Total Width (with discharge chute in mowing position):**
- 52" models: 64.5"
 - 61" models: 73.5"
 - 72" models: 83"
- Total Width (with discharge chute in transport position):**
- 52" models: 53"
 - 61" models: 62"
 - 72" models: 73"
- Height (with ROPS):** 67.5"
- Height (with ROPS folded):** 56.5"
- Weight (with ROPS):**
- 52" models: 1250 lbs.
 - 61" models: 1350-1445 lbs.
 - 72" models: 1400-1495 lbs.
- Warranty:**
- 2 Yr. Mower Warranty—Parts & labor.
 - 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
 - 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
 - 2 Yr. Engine Warranty—Minimum of a two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice.

WWW.SCAG.COM