

WILDCAT



Powerful mowing in a compact package.

Specifications

Engine Options:

- 25hp Kawasaki, air-cooled, twin cylinder, vertical shaft
- 26hp Kawasaki, liquid-cooled, twin cylinder, vertical shaft
- 27hp Kohler, air-cooled, twin cylinder, vertical shaft
- 30hp Kohler, air-cooled, twin cylinder, vertical shaft

Fuel Capacity/Design:

8 gallons, dual fuel tanks with molded-in cupholder.

Travel Control:

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes.

Ground Speed:

10mph forward, 4.5mph reverse

Main Frame Construction:

Steel tube frame, full length, fully welded

Drive Tires:

- 52": 23 x 9.5 -12, 4 ply
- 61": 24 x 12 - 12, 4 ply

Caster Tires:

13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Hydraulic Pumps:

Dual Pumps; 10cc displacement, Hydro-Gear BDP-10A

Hydraulic Oil Cooler:

Yes - Cooling reservoir with auxiliary oil cooler

Hydraulic Oil Filter:

10 micron

Hydraulic Wheel Motors:

Dual Hydro-Gear Danfoss 15ci heavy-duty motors with extra large shafts

Electrical System:

12 Volt battery. Alternator, 15amp charging. Solenoid shift starter.

- Belts:** Kevlar cord. Self-adjusting, spring-loaded self-tightening
- Drive/Load Pulleys:** Split-steel design -- stronger and lighter weight than cast-iron
- Instrument Panel :** Key switch, throttle, manual choke, BBC switch
- Seat:** Mid-back Soft-Ride seat, adjustable with padded arm rests.
- PTO - Electric Clutch:** Ogura GT3.5 - 250 ft lb / adjustable air-gap
- Cutter Decks:** 52" & 61" Velocity Plus Decks. Floating, adjustable, anti-scalping design.
- Cutter Deck Construction:** Tri-Plate, welded: 52" with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates. 61" with 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.
- Cutter Deck Drive:** Belt driven -- Straight belt for long life, not a twisted "mule" drive
- Number of Anti-Scalp Wheels:**
- 52": 4 wheels in 4 positions
 - 61": 7 wheels in 5 positions
- Cutter Deck Spindles:** Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
- Cutter Deck Height Adjustment:** Foot pedal lift with self-locking mechanism at transport position
- Cutting Range:** 1-1/4" to 5-1/2" in 1/4" increments
- Number of Cutter Blades:** 3 Marbain blades
- Total Length:**
- 52" models: 80"
 - 61" models: 83"
- Total Width (with discharge chute in mowing position):**
- 52" models: 64.5"
 - 61" models: 73.5"
- Total Width (with discharge chute in transport position):**
- 52" models: 53"
 - 61" models: 62"
- Height (with ROPS):** 66"
- Height (with ROPS folded):** 54"
- Weight (with ROPS):**
- 52" models: 1100 lbs.
 - 61" models: 1200-1210 lbs.
- Warranty:**
- 2 Yr. Mower Warranty—Parts & labor.
 - 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
 - 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
 - 2 Yr. Engine Warranty—Minimum of a two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice.

WWW.SCAG.COM